

## Specification

Model	Capacity (kVA)	Phase	Frequency (Hz)	Input voltage (V)	Output voltage (V)	Max. output current (A)	Shape	
TDGC2,TDGC-0.2/0.5(M)	0.2	1	50/60	110/ 220	0-250	0.36/0.8	Round	
TDGC2,TDGC-0.25/0.5(M)	0.25					0.4/1		
TDGC2,TDGC-0.5/0.5(M)	0.5					0.88/2		
TDGC2,TDGC-0.5(C)	0.5					0.88/2		
TDGC2,TDGC-1/0.5	1					1.6/4		
TDGC2,TDGC-2	2					3.2/8		
TDGC2,TDGC-3/0.5	3					4.8/12		Hexagon
TDGC2,TDGC-5/0.5	5					8/20		Round
TDGC2,TDGC-10/0.5	10					16/40		Octagon
TDGC2,TDGC-15/0.5	15					24/60		
TDGC2,TDGC-20/0.5	20					80		
TSGC2,TSGC-3/0.5	3					3		50/60
TSGC2,TSGC-6/0.5	6	3.2/8						
TSGC2,TSGC-10/0.5	10	5.4/13.4	Octagon					
TSGC2,TSGC-15/0.5(M)	15	20						
TSGC2,TSGC-20/0.5(M)	20	28						
TSGC2,TSGC-30/0.5(M)	30	40						

Model	Dimmension(mm)									Weight Kg	
	L2	L1	H	H1	h	φ	d	D	R		
TDGC2	-0.2	130	115	125	90	23	100	4	8	2.2	
	-0.5	150	132	136	98	23	116	4	8	3.5	
	-1	207	182	158	120	30	156	5	12	6.1	
	-2	207	822	190	140	30	156	5	12	8.3	
	-3	235	210	198	140	36	190	6	12	11	
	-4	272	245	248	182	36	218	8	16	13.5	
	-5	300	245	248	182	36	218	8	16	15.5	
	-10	350	320	262	192	36	290	8	16	27	
	-15	395	320	505	420	36		10	16	172.5	51
TSGC2	-3	207	182	450	396	30		8	12	92	19
	-6	240	182	558	490	30		8	12	92	26
	-9	270	210	567	490	36		8	12	112	33
	-15	305	245	681	616	36		10	16	131	49