

Photointerrupter

■ PS46XX family

Type number	Current transfer ratio			Features
	CTR (%)	I _F (mA)	V _{CE} (V)	
PS4601	1.5 ~	5	2	Small all-in-one type (2.5 mm thick) Single transistor output
PS4602	1.5 ~	5	2	Small all-in-one type (PS4601 with light shield case) Single transistor output
PS4602(1)	1.5 ~	5	2	Small all-in-one type (PS4602 short lead type) Single transistor output
PS4651	40 ~	5	2	Small all-in-one type (2.5 mm thick) Darlington transistor output
PS4652	40 ~	5	2	Small all-in-one type (PS4651 with light shield case) Darlington transistor output
PS4652(1)	40 ~	5	2	Small all-in-one type (PS4652 short lead type) Darlington transistor output

PS4601



■ PS47XX Family

Type number	Current transfer ratio			Features
	CTR (%)	I _F (mA)	V _{CE} (V)	
PS4701 PS4702	5 ~	5	0.6	Miniature type (4 x 4 x 4 mm) Single transistor output Light receiving window: 0.3mm slit
PS4703	1.3 ~	10	0.6	Snap-in type Single transistor output Light receiving window: 0.5mm slit
PS4704	1.0 ~	10	0.6	Miniature type (3.8 x 4 x 4 mm) Single transistor output Light receiving window: 0.15mm slit
PS4751 PS4752	100 ~	5	2	Miniature type (4 x 4 x 4 mm) Darlington transistor output Light receiving window: 0.3mm slit

PS4701

