



**J201  
J202**



**MMBFJ201  
MMBFJ202**



## N-Channel General Purpose Amplifier

This device is designed primarily for low level audio and general purpose applications with high impedance signal sources. Sourced from Process 52.

### Absolute Maximum Ratings\*

TA = 25°C unless otherwise noted

Symbol	Parameter	Value	Units
V <sub>DG</sub>	Drain-Gate Voltage	40	V
V <sub>GS</sub>	Gate-Source Voltage	- 40	V
I <sub>GF</sub>	Forward Gate Current	50	mA
T <sub>J</sub> , T <sub>stg</sub>	Operating and Storage Junction Temperature Range	-55 to +150	°C

\*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

#### NOTES:

- 1) These ratings are based on a maximum junction temperature of 150 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations

### Thermal Characteristics

TA = 25°C unless otherwise noted

Symbol	Characteristic	Max		Units
		J201 / J202	*MMBFJ201	
P <sub>D</sub>	Total Device Dissipation Derate above 25°C	625	350	mW
		5.0	2.8	mW/°C
R <sub>θJC</sub>	Thermal Resistance, Junction to Case	83.3		°C/W
R <sub>θJA</sub>	Thermal Resistance, Junction to Ambient	200	357	°C/W

\* Device mounted on FR-4 PCB 1.6" X 1.6" X 0.06."

# N-Channel General Purpose Amplifier

(continued)

J201 / J202 / MMBFJ201 / MMBFJ202



## Electrical Characteristics

TA = 25°C unless otherwise noted







Symbol	Parameter	Test Conditions	Min	Max	Units
<b>OFF CHARACTERISTICS</b>					
$V_{(BR)GSS}$	Gate-Source Breakdown Voltage	$I_G = -1.0 \mu A, V_{DS} = 0$	-40		V
$I_{GSS}$	Gate Reverse Current	$V_{GS} = -20 V, V_{DS} = 0$		-100	pA
$V_{GS(off)}$	Gate-Source Cutoff Voltage	$V_{DS} = 20 V, I_D = 10 nA$	J201 -0.3 J202 -0.8	-1.5 -4.0	V V
<b>ON CHARACTERISTICS</b>					
$I_{DSS}$	Zero-Gate Voltage Drain Current*	$V_{DS} = 20 V, I_{GS} = 0$	J201 0.2 J202 0.9	1.0 4.5	mA mA
<b>SMALL SIGNAL CHARACTERISTICS</b>					
$y_{fs}$	Forward Transfer Admittance	$V_{DS} = 20 V, f = 1.0 kHz$	J201 500 J202 1000		$\mu mhos$ $\mu mhos$

\*Pulse Test: Pulse Width  $\leq 300 \mu s$


## Typical Characteristics







Typical Characteristics (continued)







Typical Characteristics (continued)



Common Source Characteristics



Common Gate Characteristics



**N-Channel General Purpose Amplifier**  
(continued)

**J201 / J202 / MMBFJ201 / MMBFJ202**